



### 铭客CT1100钢带由硬化碳钢制成具有以下特点:

MINGKE CT1100 steel belt is made of hardened carbon steel and is characterized by:

- 良好的静态强度 Good static strength
- 优异的耐磨性 Excellent wear resistance
- 极好的疲劳强度 Very good fatigue strength
- · 良好的可维修性 Good repairability
- 极好的导热性能 Very good thermal properties

CT1100具有坚硬、光滑的表面和黑色氧化层,使其适用于腐蚀风险低的任何应用。极好的导热 性能使其非常适合用于烘烤以及液体,糊状和细粒产品的加热和干燥。

CT1100 has hard & smooth surface and a black oxide layer, which makes it suitable for any application with a low risk for corrosion. Very good thermal properties make it ideal for baking and for heating and drying of liquids, pastes and fine-grained products.

### 化学成分(公称值)

Chemical Composition (Nominal) %

碳 C	硅 Si	锰 Mn	磷Ρ	硫 S	铬 Cr	铜 Cu	镍 Ni	铝 Al	铁 Fe
0.65	0.24	1.00	<0.03	0.002	0.22	0.02	0.01	0.022	-

### 静态强度

## 室温下的标准强度(公称数值)

Static Strength

Standard strength at room temperature (nominal values)

参量 Parameters	抗拉强度 Tensile strength		屈服强度 Yield strength		延伸率 Elongation	焊接系数 Weld factor	硬度 Hardness
	Мра	Ksi	Мра	Ksi	A5(%)	Rm/Rm	HV5
母材 Parent material	1080	157	960	139	8	*	340
焊接区域 Welding area	800	116	650	94	5	0.75	*

# 供货范围

**Scope of Supply** 

长度 Length: 可定制 customize available

宽度 Width: 600 / 800 / 1000 / 1200 / 1500 / ... mm

厚度 Thickness: 0.8/1.2/1.4/1.5 mm

提示: 单幅钢带最宽宽度 1500mm, 超过此宽度需要纵向拼接。特殊规格可以定制。

Tips: Max. width of a single belt is 1500mm, customized sizes via cutting or longitudinal welding are available.

<sup>\*</sup> 本资料中数据具代表性但并不受到绝对保证。数据亦会因材料批次不同而改变。

<sup>\*</sup> The data in this sheet are typical values, but not guaranteed. The information is subject to changes in different batches of material.